

### Erstklassiger Scheibenklebstoff Colle Pare-Brise PREMIUM

#### Premium autoruitenkit

- 30 min. sichere Wegfahrzeit (SDAT), All-in-one Modul, nir rige Leitfähigkeit, kalt applizierbar
- ▶ Temps de libération du véhiti le : 30 min, Adapté pour tous modèles de véhicules, Faible conductivité, Application à froid
- Veilige wegrijtijd van 30 mini ten, All-in-one modulus, Laaggeleidend, Koud toepas baar



# SikaTack® PRO PREMIUM CHOICE FOR AUTO GLASS PROFESSIONALS

- True 30 min Safe Drive-Away Time
- Safe Drive-Away Time valid for all climates
- Compatible with all car makes due to Sika's all-in-one technology
- Compatible with Sika's Black-Primerless and All-Black bonding process



When using SikaTack® PRO, you can rely on Sika's expertise and knowledge as OEM supplier and world leader in windshield adhesives. At Sika we are committed to keep the installation process simple and to deliver an additional safety margin for you and your customer.

### **SAFETY WITHOUT COMPROMISE**

Sika is the one and only adhesive manufacturer world-wide using a 95<sup>th</sup> percentile crash test dummy. Due to the use of a heavier dummy, our tests can cover a higher percentage of people worldwide.

## ALL-BLACK UND BLACK-PRIMERLESS INSTALLATION PROCESS

SikaTack® PRO is compatible with both installation processes offered by Sika. The Black-Primerless delivers the fastest application process for the standard auto glass related applications whereas using the All-Black solution lets you keep inventories smaller by just using one Pre-Treatment product for all process steps.



WITH SIKA YOU ARE ON THE HIGH ROAD TO SAFETY.

PRE-TREAMENT PROCEDURES	BLACK-PRIMER- LESS PROCESS	ALL-BLACK PROCESS
Float glass and ceramic coated glass		
Bare metal scratches < 5 cm <sup>2</sup>		
Bare metal scratches 5 cm <sup>2</sup> to 150 cm <sup>2</sup>		
Intact OEM and aftermarket paint*		
PVC & RIM encapsulation		
Trimmed residual bead		optional /
Pre-applied adhesive system		optional /
PMMA/PC**		

Sika® Aktivator PROSika® Primer-207

\*after complete curing of the paint
\*\*additional UV protection required
For details check installation process charts
(available separately)

Our most current General Sales Conditions shall apply.
Please consult the Data Sheet prior to any use and processing.







